# Practical course using the R software

# Disease outbreak analysis using $\mathbf{Q}$

 $Thibaut\ Jombart\ (tjombart@imperial.ac.uk)$ 

#### Abstract

This tutorial introduces different tools, from exploratory approaches to model-based methods, for the analysis of pathogen genome data collected during disease outbreaks, using the software [5]. We illustrate how different approaches including phylogenetics, genetic clustering, SeqTrack [3] and outbreaker [2] can be used to uncover the features of a disease outbreak, and possibly help designing containment strategies. This tutorial uses the packages ape [4] for phylogenetic analyses, adegenet [1] for genetic clustering and quick transmission tree reconstruction (SeqTrack algorithm), and outbreaker [2] for advanced reconstruction of epidemics. While the data and analysed outbreak are purely fictional, the methodology presented here will be useful for a range of actual disease outbreaks.



# Contents

1	Introduction  1.1 An emerging pathogen outbreak	<b>3</b> 3	
<b>2</b>	First look at the data	4	
3	Phylogenetic analysis	7	
4	Identifying clusters of cases	8	
5	Analysis using $SeqTrack$	10	
6	Detailed outbreak reconstruction using outbreaker 6.1 outbreaker analysis	12 12 23	
7	Update from detailed case investigations	31	

# 1 Introduction

# 1.1 An emerging pathogen outbreak

A new virus has just emerged in the small city of Arkham, Massachusetts (USA), causing an outbreak of a very peculiar and unique disease. The most common symptoms include dementia and to varying extent fever, resulting in frequently attempted cannibalism and subsequent isolation of the patients (Figure 1).



Figure 1: Example of a "mild" case.

Unfortunately, in a smaller number of more concerning cases the patients were seen to grow fangs, claws, and various numbers of tentacles and pseudopods, and were subsequently shot by the police forces (Figure 2). Authorities refer to the two types of cases as "mild" and "severe", respectively.



Figure 2: Example of a "severe" case.

# 1.2 Your objective

An expert in the analysis of disease outbreaks, you have been mandated for the analysis of the first collected data. So far, the mode of transmission of the disease is not obvious, but the pathogen has been identified as a virus, and its genome sequenced. Your task is to exploit this information to cast some light on who infected whom.

# 2 First look at the data

We first load the R packages used for the analysis of the data: *ape* (for phylogenetics), *adegenet* (for genetic clustering and *SeqTrack*), and *outbreaker* (for detailed outbreak reconstruction).

```
> library(ape)
> library(adegenet)
> library(outbreaker)
```

The data consist of two files: the file cases.csv containing descriptions of the first 30 cases sampled so far, and a DNA alignment in fasta format (alignment.fa) containing one viral genome sequence for each case. We read these data directly from the server where they are available, starting with cases descriptions:

> cases <- read.csv("http://adegenet.r-forge.r-project.org/files/fakeOutbreak/cases.csv")
> cases

```
id collec.dates sex age peak.fever outcome
1 2013-02-18 m 30 37.5 mild
                                                                             notes
1
2
          2013-02-20
                             40
                                        38.5
     2
                         f
                                                  mild
     3
         2013-02-21
                         f
                             32
                                        38.0
                                                  mild
4
          2013-02-21
                             35
                                        38.5
                                                  mild
                         m \\
          2013-02-22
     5
                         f
                              3
                                        39.5
                                                  mild
67
     6
7
          2013-02-24
                         f
                             34
                                        39.0
                                                  mild
         2013-02-23
                             61
                                        40.0
                         \mathbf{m}
                                               severe
8
    8
          2013-02-24
                         f
                             68
                                        39.5
                                               severe
          2013-02-24
9
     9
                         m
                             35
                                        39.5
                                                  mild
10 10
          2013-02-24
                         f
                                        39.5
                                                  mild
          2013-02-26
                         m
f
                             26
                                        39.0
11
   11
                                                  mild
12
   12
          2013-02-25
                                        37.5
                             69
                                               severe
          2013-02-25
13 13
                         m
                             19
                                        40.5
                                                  mild
14
   14
          2013-02-25
                         f
                             66
                                        37.5
                                                  mild
15 15
          2013-02-25
                         f
                              3
                                        37.0
                                                  mild
16
   16
          2013-02-26
                             19
                                        37.0
                         m
                                                  mild
17
                                        38.5
   17
          2013-02-26
                             35
                         m
                                                  mild
          2013-02-27
18 18
                             37
                                        37.0
                                                  mild
                         m
          2013-02-26
19
   19
                             11
                                        37.5
                         m
                                                  mild
   20
21
22
20
          2013-02-28
                             35
                                        37.5
                                                  mild
                         m
21
22
          2013-02-27
                         m
                             49
                                        37.0
                                                  mild
          2013-02-28
                             35
                                        37.0
                                                  mild
                         m
23 23
24 24
          2013-02-26
                         m
                             34
                                        37.0
                                                  mild
          2013-02-27
                             59
                                        37.5
                                               severe
25 25
          2013-02-26
                             47
                                        37.0
                         f
                                                  mild
26
   26
          2013-02-26
                         f
                             34
                                        37.0
                                                  mild
27
   27
          2013-02-28
                         f
                             26
                                        37.5
                                                  mild
          2013-02-27
                                                        possible-contamination
28 28
                         f
                             16
                                        37.0
                                                  mild
29
   29
          2013-03-01
                         f
                             15
                                        41.0
                                                  mild
30 30
          2013-03-01
                                        37.0
                                                  mild
```

The data contain the following fields: id is the identifier of the cases, collec.dates are collection dates (in format yyyy-mm-dd), the gender (sex) and age (age) of the patients, the highest temperature of the case (peak.fever), and the outcome of the case (outcome). The additional field notes has been used for notes on the samples, and indicates that sample 28 might have experienced DNA contamination (possible mixture of different samples).

As operations on the collection dates will be useful, we convert the dates (originally as character strings) into Date objects; we also create a new object days, which gives collection times in number of days after the first sample (which has been sampled, by definition, on day 0):


```
> dates <- as.Date(cases$collec.dates)
> head(dates)

[1] "2013-02-18" "2013-02-20" "2013-02-21" "2013-02-21" "2013-02-22"
[6] "2013-02-24"

> range(dates)
```

```
[1] "2013-02-18" "2013-03-01"
> days <- as.integer(difftime(dates, min(dates), unit="days"))</pre>
> days
                      6 5 6 6 6 8 7 7 7 7 8 8 9 8 10 9 10 8 9 8
[26] 8 10 9 11 11
   DNA sequences for the 30 cases are read from the server using fasta2DNAbin:
> dna <- fasta2DNAbin("http://adegenet.r-forge.r-project.org/files/fakeOutbreak/alignment.fa")</pre>
 Converting FASTA alignment into a DNAbin object...
 Finding the size of a single genome...
 genome size is: 10,000 nucleotides
( 168 lines per genome )
 Importing sequences...
Forming final object...
...done.
> dna
30 DNA sequences in binary format stored in a matrix.
All sequences of same length: 10000
Labels: 1 2 3 4 5 6 ...
Base composition:
a c g t
0.251 0.242 0.251 0.256
   To have an idea of the existing diversity in these sequences, we compute the
simple pair-wise Hamming distances and plot their distribution:
> D <- dist.dna(dna, model="N")</pre>
> hist(D, col="royalblue", nclass=30,
+ main="Distribution of pairwise genetic distances",
       xlab="Number of differing nucleotides")
```

# Distribution of pairwise genetic distances



For such a small temporal scale and genome, the amount of diversity is considerable. The fact that the distribution is clearly bimodal suggests the existence of at least two clades (and possibly more).

It may be interesting to see if this remarkable polymorphism is distributed randomly across the genome. We can extract SNP positions very simply from the DNA sequences using seg.sites:


```
> snps <- seg.sites(dna)
> head(snps)
```

## [1] 142 161 226 236 313 331

> length(snps)

#### [1] 79

There are 79 polymorphic sites in the sample. We can visualize their position, and try to detect hotspots of polymorphism by computing the density of SNPs as we move along the genome:



Here, the polymorphism seems to be distributed fairly randomly.

# 3 Phylogenetic analysis

The genetic relationships between a set of taxa are typically inferred using phylogenetic trees. Here, we reconstruct a phylogeny using the usual Neighbour-Joining algorithm on pairwise genetic distances. As the mere number of differing nucleotides may be too crude a measure of genetic differentiation, we use Tamura and Nei's distance, which handles different rates for transitions and transversions (see <code>?dist.dna</code> for other available distances):

```
> D.tn93 <- dist.dna(dna, model="TN93")</pre>
```

The package ape makes the construction of phylogenies from distances matrices easy; in the following, we create a Neighbour-Joining tree (nj) based on our new distance matrix (D.tn93), we root this tree to the first sample (root), and ladderize it to make it prettier (ladderize):

```
> tre <- root(tre,1)
> tre <- ladderize(tre)</pre>
```

We also rename the tips of the tree (tre\$tip.label) to include the collection dates after the case indices:


```
> tre$tip.label <- paste("Case ",1:30, " / day ", days, sep="")</pre>
```

Finally, we plot the resulting tree, using colors to represent collection dates (blue: ancient; red: recent):

```
> plot(tre,edge.width=2, tip.col=num2col(days, col.pal=seasun))
> title("Neighbour-Joining tree (TN93 distances)")
> mtext(side=3, text="(rooted to first case)")
```

## Neighbour-Joining tree (TN93 distances)

(rooted to first case)



How many clades are there? Is this tree clock-like? Is rooting to the first sample appropriate? What other graphical representation would you recommend?

# 4 Identifying clusters of cases


Identifying clusters of cases from a phylogeny is not always straightforward. Adegenet implements a simple clustering approach based on the number of mutations separating sequences, classifying them in the same cluster if their distance is less than a given threshold. This function is called **gengraph**, and can be used with an interactive mode (by default), using:

```
> clust <- gengraph(D)</pre>
```

(legend: sequences are the nodes of the graphs; edges link sequences from the same cluster; numbers on the edges indicate numbers of mutations)

Try a few values; you should see that 3 groups are obtained for anything between 15 and 25 mutations, with the result looking like this:

## Clusters obtained by gengraph



> plot(clust\$g, main="Clusters obtained by gengraph")






> cases[28,]

This confirms what the phylogeny suggested: there are two distinct clades, and one outlier (case 28), which is very likely an indication that this sample was indeed contaminated — as a reminder:

# Neighbour-Joining tree (TN93 distances)

(unrooted tree)



# 5 Analysis using SeqTrack

The phylogenetic tree gives us an idea of the possible chains of transmissions, but overlooks the collection dates. The SeqTrack algorithm has been designed to fill this gap. It aims to reconstruct ancestries between the sampled sequences based on their genetic distances and collection dates, so that the obtained tree has maximum parsimony. It is implemented in adegenet by the function seqTrack (see ?seqTrack). Here, we use SeqTrack on the matrix of pairwise distances (distmat), indicating the labels of the cases (x.names=cases\$id) and the collection dates (x.dates=dates):

```
> distmat <- as.matrix(D)
> sqtk.res <- seqTrack(distmat, x.names=cases$id, x.dates=dates)
> class(sqtk.res)
```

[1] "seqTrack"

"data.frame"


seqTrack objects can be plotted simply using:

> g <- plot(sqtk.res, main="SeqTrack reconstruction of the outbreak")
> mtext(side=3, text="red: no/few mutations; grey: many mutations")

```
> sqtk.res
   id ances weight
                              date ances.date
                   NA 2013-02-18
           NA
                                            <NA>
                      2013-02-20 2013-02-18
    23
2345678
            2
                       2013-02-21
                                    2013-02-20
                   26 2013-02-21
                                    2013-02-18
    4
5
6
7
8
                       2013-02-22
2013-02-24
            3
                                    2013-02-21
            4
                                    2013-02-21
            4
                       2013-02-23
                                    2013-02-21
                       2013-02-24
                                    2013-02-22
            5
                       2013-02-24
     9
                                    2013-02-21
                       2013-02-24
2013-02-26
                                    2013-02-21
2013-02-21
10
   10
            4
   11
12
            4
5
9
11
                    ō
12
                       2013-02-25
                                    2013-02-22
13
   13
                       2013-02-25
                                    2013-02-24
   14
            5
                       2013-02-25
                                    2013-02-22
                      2013 02-25
2013-02-25
2013-02-26
2013-02-26
   15
            5
15
                                    2013-02-22
   16
17
            44
16
                                    2013-02-21
17 17
18 18
                                    2013-02-21
            5
                       2013-02-27
                                    2013-02-22
19
   19
            9
                       2013-02-26 2013-02-24
20
21
22
23
24
                       2013-02-28
2013-02-27
   20
           10
                                    2013-02-24
  21
22
23
24
                                    2013-02-26
           11
                       2013-02-28
                                    2013-02-26
           11
                       2013-02-26
                                    2013-02-25
           13
           13
                       2013-02-27 2013-02-25
25
26
  25
26
                       2013-02-26 2013-02-25
2013-02-26 2013-02-21
           13
            4
27 27
28 28
                       2013-02-28
           17
                                    2013-02-26
                                    2013-02-18
                   28
                       2013-02-27
            1
   29
           10
                       2013-03-01 2013-02-24
                       2013-03-01 2013-02-25
The result sqtk.res is a data.frame with the special class seqTrack, containing
the following information:
   * sqtk.res$id: the indices of the cases.
   * sqtk.res$ances: the indices of the putative ancestors of the cases.
   * sqtk.res$weight: the number of mutations for each putative ancestry.
   * sqtk.res$date: the collection dates of the cases.
   * sqtk.res$ances.date: the collection dates of the putative ancestors.
```

## SeqTrack reconstruction of the outbreak

red: no/few mutations; grey: many mutations



#### > g

```
IGRAPH DNW- 30 29 -- + attr: name (v/c), dates (v/n), weight (e/n), label (e/n), color (e/c)
```

Each sequence/case is a node of the graph, and arrows model putative ancestries/transmissions. The number of mutations between ancestors and descendents are indicated by the color of the arrows (red = no/few mutations; light grey= many mutations) and the numbers in blue. Time is represented on the y axis (up: ancient; down: recent). Note that the function plot invisibly returns a graph object which can be used for further visualization. In particular, tkplot offers a basic interface for interactive graphics which you can try using:

#### > tkplot(g)

One of the (several) limitations of SeqTrack is made quite obvious here: all sequences are forced to coalesce to the initial one, while there are some clearly distinct clusters indicative of two separate introductions (cases 1 and 4).

# 6 Detailed outbreak reconstruction using outbreaker

# 6.1 *outbreaker* analysis

The SeqTrack algorithm provides a single, parsimonious reconstruction of the disease transmission tree, based on the pathogen sequences and the temporal ordering

of their collection dates. While useful, it still represents a very incomplete reconstruction of the outbreak: it assumes a single introduction of the disease, does not take the time interval between cases into account, does not estimate dates of infections, overlooks alternative yet likely transmissions, and does not provide statistical support for individual ancestries. *outbreaker* [2] has been developed to address these issues.

This method exploits information on pathogen genomes, collection dates and (possibly vague) information about the generation time (time interval between primary and secondary cases) to reconstruct the outbreak, including likely dates of infections and ancestries. In the present case, we do not possess external sources of information about the generation time distribution, but a fairly uninformative distribution can be constructed. Here, we want this distribution to meet two properties:


- \* not exclude a priori any transmission in the outbreak; in other words, the probability of the longest possible time interval must be non-zero.
- \* be monotonically decreasing, i.e. longer time intervals between transmissions are given smaller probabilities; this will force shorter transmission chains, which is consistent with the very short time intervals observed between the first cases of the outbreak.

Given the short time span of the outbreak:

```
> range(days)
[1] 0 11
> head(days)
[1] 0 2 3 3 4 6
```

we use an exponential distribution to model the generation time distribution:

#### Generation time distribution



We now run outbreaker, providing as input the DNA sequences, their collection dates (in days since the first sample), and generation time distribution; as we are confident that every cases have been observed, we fix the number of generations between consecutive cases to be one (move.kappa=FALSE and init.kappa fixed to 1); finally, we use a star-like tree to initialize the MCMC:

The object obkr.res is a list with a number of named items, described in ?outbreaker. The most important one is obkr.res\$chains, containing the MCMC outputs:

14

```
> class(obkr.res$chains)
[1] "data.frame"
```

> dim(obkr.res\$chains)

```
[1] 201 99
```

#### > names(obkr.res\$chains)

```
[1] "step"
                  "post"
                              "like"
                                           "prior"
                                                        "mu1"
                                                                     "mu2"
                                           "Tinf_2"
     "gamma"
                  "pi"
                              "Tinf_1"
                                                        "Tinf_3"
                                                                    "Tinf_4"
[7]
     "Tinf_5"
                  "Tinf_6"
                               "Tinf_7"
                                           "Tinf_8"
                                                        "Tinf_9"
                                                                     "Tinf_10"
[13]
     "Tinf_11"
                  "Tinf_12"
                              "Tinf_13"
                                           "Tinf_14"
                                                        "Tinf_15"
                                                                     "Tinf_16"
[19]
                 "Tinf_18"
"Tinf_24"
"Tinf_30"
                                           "Tinf_20"
"Tinf_26"
                                                        "Tinf_21"
"Tinf_27"
     "Tinf_17"
                              "Tinf_19"
                                                                     "Tinf_22"
[25]
     "Tinf_23"
"Tinf_29"
                              "Tinf_25"
                                                                     "Tinf_28"
[31]
Γ37<sup>1</sup>
                              "alpha_1"
                                           "alpha_2"
                                                        "alpha_3"
                                                                    "alpha_4"
     "alpha_5"
                              "alpha_7"
                                                        "alpha_9"
[43]
                  "alpha_6"
                                           "alpha_8"
                                                                    "alpha_10"
[49] "alpha_11"
                 "alpha_12"
                              "alpha_13"
                                           "alpha_14"
                                                        "alpha_15"
                                                                    "alpha_16"
[55]
     "alpha_17"
                 "alpha_18"
                              "alpha_19"
                                           "alpha_20"
                                                        "alpha_21"
                                                                    "alpha_22"
[61] "alpha_23"
                  "alpha_24"
                                                        "alpha_27"
                                                                    "alpha_28"
                              "alpha_25"
                                           "alpha_26"
[67]
     "alpha_29"
                  "alpha_30"
                              "kappa_1"
                                           "kappa_2"
                                                        "kappa_3"
                                                                    "kappa_4"
                              "kappa_7"
                                                        "kappa_9"
[73]
     "kappa_5"
                  "kappa_6"
                                           "kappa_8"
                                                                    "kappa_10"
                              "kappa_13"
[79]
     "kappa_11"
                 "kappa_12"
                                           "kappa_14"
                                                        "kappa_15"
                                                                    "kappa_16"
[85]
     "kappa_17"
                 "kappa_18"
                              "kappa_19"
                                           "kappa_20"
                                                        "kappa_21"
                                                                    "kappa_22"
     "kappa_23" "kappa_24" "kappa_25"
                                           "kappa_26"
                                                        "kappa_27"
                                                                    "kappa_28"
[91]
[97] "kappa_29" "kappa_30"
```


#### > obkr.res\$chains[1:10,1:10]

```
post
-1887.9314
                       like prior mu1 mu2 -1888.5632 0.6317343 5.000000e-05 5.000000e-05
                                                                                 gamma
1.0000000
23
     500
           -180.7824
                        -181.6428
                                    0.8604325
                                                 5.015320e-05
                                                                 2.068721e-05 0.4124804
   1000
           -187.8066
                        -188.2122
                                     0.4055156 5.006900e-05 8.663932e-06 0.1730399
           -192.9006
4
                        -193.3492 0.4485830 4.985273e-05 1.608505e-05 0.3226513
   1500
5
                        -186.7201 0.5200072 4.932467e-05 3.004623e-05 0.6091523 -189.0329 0.8333027 4.971446e-05 2.003563e-05 0.4030141
   2000
           -186.2000
                        -189.0329 0.8333027 4.971446e-05 2.003563e-05 0.4030141 -188.2209 0.9214907 4.990173e-05 2.305008e-05 0.4619093
6
    2500
           -188.1996
    3000
           -187.2994
                        -194.5370 0.6641120 4.969108e-05 1.789834e-05 0.3601922
   3500
           -193.8729
                        -182.2536 0.6391482 5.224465e-05 2.208487e-05 0.4227201
   4000
           -181.6145
                        -182.9857 0.4630125 5.557073e-05 1.028319e-05 0.1850469
10 4500
           -182.5227
            pi Tinf_1 Tinf_2
   0.9770704
   0.9946895
                               1
   0.9909562
                              -4
                    -11
                             -4
   0.9576260
                             -2
   0.9543718
   0.9922438
   0.9993152
                             -1
   0.9769004
   0.9700053
   0.9918120
```

The columns of this data.frame store the following outputs:

- ★ step: the MCMC iteration of the sample
- \* post/like/prior: log values for posterior, likelihood, and prior densities
- \* mul: rate of transitions, per site and generation
- ★ mu2: rate of transversions, per site and generation
- $\star$  gamma: the ratio between transversions and transitions  $(\mu_2/\mu_1)$
- ★ pi: the proportion of the transmission tree sampled
- $\star$  Tinf\_[number]: dates of infection
- \* alpha\_[number]: the index of the ancestral cases (infectors)
- \* kappa\_[number]: the number of generations between cases and their most recent sampled ancestor (here, fixed to 1)
- \* run: for parallel runs, the index of the run.


Convergence of the chain and distributions of parameters can be visualized using plotChains (see ?plotChains for details):



One can easily derive statistics from posterior samples to get e.g. credibility intervals. For instance, the overall mutation rate (sum of the two rates) is obtained, after discarding a burnin of 20,000 iterations, by:

```
> mu <- (obkr.res$chains$mu1+obkr.res$chains$mu2)[obkr.res$chains$step>2e4]
> hist(mu, col="royalblue", main="Posterior distribution of the mutation rate",
+ xlab="Mutations per site and generation")
```

#### Posterior distribution of the mutation rate



Mutations per site and generation


Its mean and 95% credibility interval are:

```
> quantile(mu*ncol(dna), c(0.025, 0.975))
```

```
2.5% 97.5%
1.018515 1.907035
```

Likely dates of infection are probably better visualized as boxplots:


#### **Estimated dates of infection**



posterior date of infection (in days after 1st sample)

The overall dynamics corresponding to these dates of infection can be summarized as incidence curves:

#### Inferred incidence




incid is a matrix containing one time series of incidence for each posterior tree. The displayed boxplot summarizes the entire posterior distribution. When did the outbreak take off? Can we trust the decrease at the end of the time series?

The posterior ancestries (columns "alpha" in res\$chains) define a graph of possible ancestries, which can be extracted and plotted using transGraph; here, we remove annotations from the edges (annot="") and retain only ancestries with a frequency  $\geq 5\%$  (thres=.05):

```
> g2 <- transGraph(obkr.res, vertex.size=10, annot="", thres=.05)
> g2

IGRAPH DN-- 30 44 --
+ attr: name (v/c), dates (v/n), label (v/n), color (e/c), support
  (e/n), curved (e/x), nb.mut (e/n), label (e/c)
```




Darker arrows correspond to well-supported ancestries, while lighter ones are more ambiguous. The object g2 is an igraph, which can be visualized interactively like before using tkplot:

## > tkplot(g2)

For some purposes, one may wish to retain only the best supported ancestries of each case. This can be achieved by <code>get.tTree</code>:


```
> obkr.tre <- get.tTree(obkr.res)
> class(obkr.tre)

[1] "tTree"
> plot(obkr.tre, vertex.size=10, edge.curved=TRUE)
```



By default, the annotations of the edges indicate number of mutations/number of generations/posterior support. See ?get.tTree for a detail of the content of obkr.tre. Note that these objects can also be converted to igraph objects using as.igraph, and implicitly using the plot method. The latter also allows for representing additional information, such as features of the cases using colors. For instance, we can represent the consensus ancestries with the outcome of the different cases:

#### **Outbreaker – consensus ancestries**



Similarly, we can represent the peak temperature of the patients:

# Peak fever 37 38 39

#### Outbreaker - consensus ancestries

While trends may be suggested from such plot, a more quantitative assessment of potential determinants of infectiousness is needed before drawing conclusions.

## 6.2 Inference from the reconstructed ancestries


One of the first concerns once we inferred a transmission tree is the identification of key individuals for the spread of the epidemic. This can be assessed by computing the number of secondary cases per infected individual, that is, the individual effective reproduction numbers  $(R_i)$ . The posterior distribution of these values can be obtained using get.R:

```
> Rmat <- get.R(obkr.res,burnin=2e4)
> class(Rmat)
[1] "matrix"
> ncol(Rmat)
[1] 30
```


40 41

Rmat is a matrix of posterior values of  $R_i$  for each of the 30 cases (in column). The distribution of  $R_i$  is obtained by:

```
> hist(Rmat, col="royalblue", nclass=20, main="Distribution of R values", + xlab="Number of secondary cases")
```



Shall we be looking for individuals driving the epidemic? The average  $R_i$  over all chains is computed using:



Now that we have this proxy for the "infectiousness" of individuals, we can try to correlate it to other factors such as age, sex, or other measured covariates. Note that we only have a snapshot of an ongoing epidemic, so we probably have not measured the infectiousness of the last infected individuals. Let us first have another look at the distribution of the collection dates:

#### case 30 case 29 case 28 case 27 case 26 case 25 case 24 case 23 case 22 0 0 0 0 Ō 0 0 0 case 21 case 20 0 0 case 19 case 18 0 0 0 case 0 case 1 case 13 case 13 case 12 case 11 Ō 0 0 0 case 11 case 10 case 9 case 8 case 7 case 6 case 5 case 4 case 3 case 2 0 0 0 0

0

4

0 0

0

2

0

0

#### Distribution of the collection dates

There is no obvious way of defining a threshold date, but keeping all cases until day 8 (included) seems to exclude most recent cases while conserving a fair portion of the sample.

Days since first sample

6

8

10

#### > toKeep <- days<9</pre>

We can now examine and test possible relationships between  $R_i$  (object Rindiv) and covariates in cases. For a reminder:


#### > head(cases)

```
id collec.dates sex age peak.fever outcome notes
1 2013-02-18 m 30 37.5 mild
         2013-02-18
                                        37.5
                                                  mild
1
2
   2
         2013-02-20
                                        38.5
                         f
                             40
                                                  mild
         2013-02-21
                         f
                            32
                                        38.0
                                                  mild
         2013-02-21
                            35
                                        38.5
                                                  mild
                         m
   5
         2013-02-22
                              3
                                        39.5
                         f
                                                  mild
         2013-02-24
                         f
                             34
                                        39.0
                                                  mild
```

Interprete the following graphs and tests:

```
> boxplot(Rindiv[toKeep]~cases$sex[toKeep], xlab="Patient gender",
       ylab="Inferred number of secondary cases caused", col=c("gold", "royalblue"))
 title("Inferred infectivity vs gender")
```

# Inferred infectivity vs gender




Patient gender


#### > t.test(Rindiv[toKeep]~cases\$sex[toKeep])

```
Welch Two Sample t-test
```


# Inferred infectivity vs age



# Inferred infectivity vs peak fever



## Inferred infectivity vs outcome



# > t.test(Rindiv~cases\$outcome)

```
Welch Two Sample t-test

data: Rindiv by cases$outcome
t = -0.0602, df = 5.724, p-value = 0.9541
alternative hypothesis: true difference in means is not equal to 0
95 percent confidence interval:
-1.063609 1.013128
sample estimates:
mean in group mild mean in group severe
0.8966346 0.9218750
```

What can you say about the transmissibility of this disease? Should prophylaxis target specific groups of individuals? Looking back at the data, especially the most recent cases:

#### > tail(cases, 10)

```
id collec.dates sex age peak.fever outcome 21 2013-02-27 m 49 37.0 mild 22 2013-02-28 m 35 37.0 mild
                                                                                                       notes
21 21
22 22
23 23
24 24
25 25
26 26
27 27
28 28
29 29
30 30
             2013-02-26
                                  \mathbf{m}
                                       34
                                                      37.0
                                                                   mild
             2013-02-27
2013-02-26
                                  m
                                       59
                                                      37.5
                                                                severe
                                                                   mild
                                       47
                                                      37.0
                                  f
f
                                                      37.0
             2013-02-26
                                       34
                                                                   mild
             2013-02-28
                                       26
                                                      37.5
                                                                   mild
             2013-02-27
                                  f
                                       16
                                                      37.0
                                                                   mild possible-contamination
             2013-03-01
                                       15
                                                      41.0
                                                                   mild
             2013-03-01
                                       40
                                                      37.0
                                                                   mild
```

Which individual(s) would you recommend isolating in priority?

# 7 Update from detailed case investigations

As you were finishing your analyses, you have been updated on the situation by the authorities. Apparently, detailed investigations have helped casting light on the transmissions that took place for the first 25 cases. Information on likely infectors is contained in the following file:

```
> newinfo <- read.csv("http://adegenet.r-forge.r-project.org/files/fakeOutbreak/update.csv")
> newinfo
```


```
infection.dates infectors
          2013-02-15
23
          2013-02-17
                                  1
          2013-02-19
                                  2
4
          2013-02-19
                                 NA
          2013-02-21
5
                                  3
6
          2013-02-21
                                  4
          2013-02-21
                                  4
          2013-02-22
8
                                  566789557789
9
          2013-02-22
          2013-02-23
10
          2013-02-23
          2013-02-23
2013-02-23
12
13
          2013-02-24
14
15
          2013-02-24
16
          2013-02-24
          2013-02-24
          2013-02-25
18
          2013-02-25
2013-02-25
19
                                 10
20
21
          2013-02-25
                                 11
22
          2013-02-25
                                 11
23
          2013-02-25
                                 13
24
          2013-02-25
                                 13
25
          2013-02-25
                                 13
```

It is fairly straightforward to compare the results of SeqTrack (sqtk.res) and outbreaker (obkr.tre) to this new data; we just need to avoid comparing NAs (as NA==NA is NA, not TRUE), so we replace unknown ancestries (NA) with 0.

```
> sqtk.res$ances[is.na(sqtk.res$ances)] <- 0</pre>
> obkr.ances <- obkr.tre$ances[1:25]
  obkr.ances[is.na(obkr.ances)] <- 0
> newinfo$infectors[is.na(newinfo$infectors)] <- 0</pre>
> comp <- rbind(sqtk.res$ances[1:25], obkr.ances, newinfo$infectors)
  rownames(comp) <- c("seqTrack", "outbreaker", "investigations")
colnames(comp) <- paste("case", 1:25)</pre>
                               2 case
                                        3 case 4 case 5 case 6 case
                                                                         7
                                                                           case 8
                                                                                          9
                  case
                          case
                                                                                   case
seqTrack
                       0
                                        2
2
2
                                                1
                                                         3
                                                                 4
                                                                         4
                                                                                 5
                                                                                          4
                                                0
                                                         3
                                                                 4
                                                                                  5
outbreaker
                       0
                                1
                                                                         4
                                                                                          6
investigations
                       0
                                                0
                                                         3
                                                                 4
                                          12
                                              case 13
                                                       case 14
                  case
                       10
                           case
                                11
                                    case
                                                                case 15 case 16
                                                                                    case
                                                                                          17
                                  4
                                            5
                                                     9
seqTrack
                                                              5
                                                                        5
                                            5
                         6
                                 21
                                                     9
                                                                                           4
outbreaker
                                                              5
investigations
                                            8
                                                     9
                       18
                                19
                                          20
                                                    21
                                                             22
                                                                       23
                                                                                24
                                                                                          25
                           case
                                    case
                                              case
                                                       case
                                                                 case
                                                                          case
                                                             11
                                                                                13
                                                                                          13
seqTrack
                         5
                                  9
                                          10
                                                    11
                                                                       13
                         5
                                  9
                                          10
                                                     4
                                                                       13
                                                                                13
                                                                                          13
outbreaker
                                                             11
                                          10
                                                                                13
                                                    11
investigations
                                                             11
> mean(comp[1,] == comp[3,])
[1] 0.68
> mean(comp[2,] == comp[3,])
[1] 0.76
```

Which method is most congruent with the new field observations, and what are the respective proportions of congruent results (inferred transmissions)? For outbreaker, one can assess easily if discrepancies are associated with weakly supported ancestries:


```
> split(obkr.tre$p.ances[1:25], obkr.ances[1:25] == newinfo$infectors)
$`FALSE
alpha_11 alpha_12 alpha_16 alpha_17 alpha_18 alpha_21 1.00000 0.61250 0.55625 0.52500 0.43125 0.50000
           0.61250 0.55625
                                 0.52500
                                            0.43125
$`TRUE`
                                                       alpha_6
0.71250
                                 alpha_4
1.00000
                                                                            alpha_8
0.70625
 alpha_1
           alpha_2
                      alpha_3
                                            alpha_5
                                                                  alpha_7
1.00000
           1.00000
                      1.000\overline{0}0
                                            1.00000
 1.00000
 alpha_9 alpha_10 alpha_13 alpha_14 alpha_15 alpha_19 alpha_20 alpha_22
1.00000 1.00000 1.00000 alpha_23 alpha_24 alpha_25
                                 0.40000
                                            0.33125
                                                       1.00000
                                                                  0.68125
                                                                             1.00000
 1.00000 1.00000 1.00000
> boxplot(split(obkr.tre$p.ances[1:25], obkr.ances[1:25]==newinfo$infectors),
            col=c("red1","royalblue"), names=c("different","congruent"),
            ylab="Support for the ancestries")
```



Let us examine again the possible effect of covariates on individual reproduction numbers  $R_i$ , this time computing  $R_i$  from the investigation data:

Again, we discard the most recent cases (collection on day 9 and later; this information is still in toKeep). What can you conclude from the following graphs and tests:

## Inferred infectivity vs gender




Patient gender


#### > t.test(Rindiv2[toKeep]~cases\$sex[toKeep])

> title("Inferred infectivity vs age")


# Inferred infectivity vs age



# Inferred infectivity vs peak fever



# Inferred infectivity vs outcome



#### > t.test(Rindiv2~cases\$outcome)

```
Welch Two Sample t-test

data: Rindiv2 by cases$outcome
t = -0.7189, df = 3.432, p-value = 0.5181
alternative hypothesis: true difference in means is not equal to 0
95 percent confidence interval:
-2.859747 1.744363
sample estimates:
mean in group mild mean in group severe
0.6923077 1.2500000
```

Are the conclusions based on these new data consistent with *outbreaker*'s results?

# References

- [1] T. Jombart. adegenet: a R package for the multivariate analysis of genetic markers. *Bioinformatics*, 24:1403–1405, 2008.
- [2] T. Jombart, A. Cori, X. Didelot, S. Cauchemez, C. Fraser, and N. Ferguson. Bayesian reconstruction of disease outbreaks by combining epidemiologic and genomic data. *Nature Communications*, submitted.
- [3] T. Jombart, R. M. Eggo, P. J. Dodd, and F. Balloux. Reconstructing disease outbreaks from genetic data: a graph approach. *Heredity*, 106:383–390, 2010.
- [4] E. Paradis, J. Claude, and K. Strimmer. APE: analyses of phylogenetics and evolution in R language. *Bioinformatics*, 20:289–290, 2004.
- [5] R Development Core Team. R: A Language and Environment for Statistical Computing. R Foundation for Statistical Computing, Vienna, Austria, 2011. ISBN 3-900051-07-0.